

# LETTER OF COMPLIANCE




**Product:** 1/2" thru 2" Maxline

**Description:** Semi-flexible compressed air piping system

**Technical Specifications:** Compressed air, vacuum, and inert gas applications  
200 psi maximum working pressure at 73°F  
160 psi maximum working pressure at 140°F  
Temp range -40°F to 140°F  
Compatible with common compressor lubricants

**General Ratings:** ASTM F1282  
ASTM F1974  
Compliant to Occupational Safety & Health Administration (OSHA)

## Tubing Specifications:



Material: inner and outer layer HDPE, center layer Aluminum  
Blue color exterior, white interior, compressed air 1/2" – 2"  
Green color exterior, white interior, inert gas 1/2" – 1"  
Trade size callout measured with I.D.

1/2" size	.63 O.D. x .50 I.D.	4-6 inch bend radius
3/4" size	.98 O.D. x .80 I.D.	8-10 inch bend radius
1" size	1.26 O.D. x 1.02 I.D.	10-12 inch bend radius
2" size	2.50 O.D. x 2.00 I.D.	36-48 inch bend radius

Life Expectancy: 50 years

## Fitting Specifications 1/2" - 1":



*Compression Style*  
Body: nickel plated brass  
Bite Ring: nickel plated brass  
O-Ring: nitrile

## Fitting Specifications 2":



*Compression Style*  
Body: nickel plated brass  
Bite Ring: stainless steel  
O-Ring: nitrile

**Engineered  
Specialties LLC**

6111 Mill Creek Drive, Auburndale, Wisconsin, 54412  
1-800-954-3310 • [www.rapidairproducts.com](http://www.rapidairproducts.com)

6/2020