

# Letter of Compliance


<b>Product Application</b>	Compressed air Inert gases such as Nitrogen, Argon, CO2 Oils, Lubricants Non-Potable Water
<b>Technical Specification</b>	Operating pressure 232 psi Operating Temperature -4°F to +176°F Vacuum Rating to 29 Hg
<b>System Ratings</b>	ASME B31.1, B31.9 ASTM B241 OSHA Compliant UL94 HB Fire resistant
<b>Rigid Pipe Specifications</b>	Aluminum alloy grade 6063 or 5052, non-chromate treated Wet Paint Blue Color RAL 5012, Green Color RAL 6018 Stainless Steel Grade 304, OD finish 0.8µm, ID 0.4µm

### Trade Size Callout Measured with O.D.

<i>3/4" size</i>	<i>20mm</i>	<i>.79 O.D. x .69 I.D.</i>
<i>1" size</i>	<i>25mm</i>	<i>.98 O.D. x .87 I.D.</i>
<i>1 1/2" size</i>	<i>40mm</i>	<i>1.57 O.D. x 1.43 I.D.</i>
<i>2" size</i>	<i>50mm</i>	<i>1.97 O.D. x 1.81 I.D.</i>
<i>3" size</i>	<i>80mm</i>	<i>3.15 O.D. x 2.98 I.D.</i>
<i>4" size</i>	<i>100mm</i>	<i>4.20 O.D. x 3.78 I.D.</i>



<b>Fitting Specification</b>	Press Type 3/4 - 4" 304 Stainless Steel body Nitrile Oring seal
------------------------------	---



PRODUCTS MANUFACTURED BY THE SELLER CARRY A LIMITED ONE YEAR WARRANTY

RapidAir Products | [www.rapidairproducts.com](http://www.rapidairproducts.com)  
 6111 Mill Creek Drive Auburndale, WI 54412 | 800-954-3310

07-2022 Rev 1