

AIR HOSE REELS

FLEXIBILITY, DURABILITY & PERFORMANCE WITHOUT COMPROMISE

RapidAir Air Hose Reels deliver industrial-grade strength, extended reach, and total control, empowering professionals to work faster and more confidently.

DUAL-ARM & SINGLE-ARM DESIGN

Available in multiple configurations, each engineered to maximize efficiency while reducing clutter

PREMIUM MATERIALS

Crafted with heavy-duty rubber for exceptional durability and flexibility

DURABLE CONSTRUCTION

Heavy-duty build ensures dependable performance in demanding work environments

SMOOTH RETRACTION


Easy-to-use retraction system provides tangle-free storage and extends hose life

VERSATILE APPLICATIONS


Choose from Industrial, Automotive or Light-Duty lines, all designed to support pneumatic tools, air compressors and other air equipment




MOUNTING OPTIONS



FLOOR, TRUCKS
AND TRAILERS



CEILING



WALL

PROFESSIONAL DUAL-ARM HOSE REEL — SLOW REWIND

- Unmatched Convenience, Performance & Safety
- 18-Gauge Powder-Coated Steel
- 12-Point Nylon Ratchet System
- Adjustable Guide Arm (225° range)
- Adjustable Swivel Roller Guide Plate (180° range)
- Slow Safety Rewind Technology
- Engineered for Reduced Retraction Noise
- Oil-Resistant (RMA Class A) Hose Resists Welding Spatter & Grinding Parts



TEMPERATURE RANGE
-30° to +190°F

WORKING PRESSURE
300 PSI

BURST PRESSURE
1200 PSI

MODEL#	ID	HOSE LENGTH	PRODUCT WEIGHT	HOSE MATERIAL	FITTINGS	REPLACEMENT HOSE
R-02050P	1/4"	50'	39 lbs	Rubber, Oil Resistant	1/4" MNPT	RH-1450-OS
R-03050P	3/8"	50'	40 lbs	Rubber, Oil Resistant	1/4" MNPT	RH-3850-OS
R-05050P	1/2"	50'	42 lbs	Rubber, Oil Resistant	1/2" MNPT	RH-1250-OS

DUAL-ARM AIR HOSE REEL

- Durable & Stable
- 18-Gauge Powder-Coated Steel
- 12-Point Nylon Ratchet System
- Adjustable Guide Arm
- Adjustable Swivel Roller Guide Plate
- Smooth Retraction & Operation
- Rugged Polyester Woven Braided Reinforcement
- 4:1 Safety Factor



TEMPERATURE RANGE
-40° to +176°F

WORKING PRESSURE
300 PSI

BURST PRESSURE
1200 PSI

MODEL#	ID	HOSE LENGTH	PRODUCT WEIGHT	HOSE MATERIAL	FITTINGS	REPLACEMENT HOSE
R-03050D	3/8"	50'	35 lbs	Rubber	1/4" MNPT	RH-3850
R-03075D	3/8"	75'	71 lbs	Rubber	1/4" MNPT	RH-3875
R-03100D	3/8"	100'	68 lbs	Rubber	1/4" MNPT	RH-38100
R-05050D	1/2"	50'	40 lbs	Rubber	1/2" MNPT	RH-1250
R-05075D	1/2"	75'	70 lbs	Rubber	1/2" MNPT	RH-1275
R-05100D	1/2"	100'	75 lbs	Rubber	1/2" MNPT	RH-12100

SINGLE-ARM AIR HOSE REEL

- Durable, Reliable & Efficient
- 20-Gauge Powder-Coated Steel
- 12-Point Nylon Ratchet System
- Single Adjustable Guide Arm
- Non-Snag Rollers for Reduced Hose Abrasion
- Ozone, Kink & Abrasion Resistant



TEMPERATURE RANGE
-40° to +176°F

WORKING PRESSURE
300 PSI

BURST PRESSURE
1200 PSI

MODEL#	ID	HOSE LENGTH	PRODUCT WEIGHT	HOSE MATERIAL	FITTINGS	REPLACEMENT HOSE
R-02025S	1/4"	25'	20 lbs	Rubber	1/4" MNPT	RH-1425
R-02035S	1/4"	35'	21 lbs	Rubber	1/4" MNPT	RH-1435
R-02050S	1/4"	50'	28 lbs	Rubber	1/4" MNPT	RH-1450
R-03025S	3/8"	25'	21 lbs	Rubber	1/4" MNPT	RH-3825
R-03035S	3/8"	35'	22 lbs	Rubber	1/4" MNPT	RH-3835
R-03050S	3/8"	50'	29 lbs	Rubber	1/4" MNPT	RH-3850
R-05025S	1/2"	25'	22 lbs	Rubber	1/2" MNPT	RH-1225
R-05035S	1/2"	35'	29 lbs	Rubber	1/2" MNPT	RH-1235
R-05050S	1/2"	50'	31 lbs	Rubber	1/2" MNPT	RH-1250

SWIVEL MOUNTS 180°

- Works with Standard 4-Hole Brackets
- Mounts Easily to Concrete, Wooden, Iron Pillars
- Wall Mountable
- Heavy-Duty Steel Construction
- Adjustable Steel Stopper Locks at Every 30°
- Corrosion-Resistant Powder Coat Finish

I CONSTRUCTION
Heavy Duty Steel

FINISH
Powder Coated

MAX WEIGHT CAPACITY
110 lbs



MODEL#	PRODUCT WEIGHT	ACCESSORIES	MATERIAL	COLOR	USE WITH REEL
SB-180S	5.3 lbs	Hex Bolt, Nut, Washer M12 mm	Steel	Blue	Small, Small Wide, Medium, Large Single-Arm Hose Reels
SB-180L	8 lbs	Hex Bolt, Nut, Washer M10 mm	Steel	Blue	Medium Dual-Arm Hose Reels
SB-180XL	18 lbs	Hex Bolt, Nut, Washer M12 mm	Steel	Blue	XL Dual-Arm Hose Reels

ACCESSORIES