

## Letter of Compliance


**Product Description:** Modular compressed air piping system 3/4" thru 8" Fastpipe

**Technical Specifications:** Compressed air, vacuum (29in-Hg), and inert gas applications  
190 psi maximum working pressure, 8" - 150 psi maximum working pressure, temp range -4°F to 176°F Compatible with common compressor lubricants

**General Ratings:**  
Conforms to ASME B31.1  
UL94HB fire resistance, compliant to OSHA

**Pipe Specifications:**  
Pipe:  
Aluminum alloy grade 6063 USA produced, 3/4"-8"  
Non-chromate treated Wet Paint  
Blue Color RAL5012 3/4"-8"  
Green Color RAL6018 outside 3/4"-2"  
Gray Color CFAB-3418 White Aluminum 3/4"-2"  
Non-chromate conversion coating inside  
Trade size callout measured with O.D.

**All Aluminum Piping  
Made in the USA**



3/4" size	20 mm	.79 O.D. x .69 I.D
1" size	25mm	.98 O.D. x .87 I.D
1 1/2" size	40mm	1.57 O.D. x 1.43 I.D
2" size	50mm	1.97 O.D. x 1.81 I.D
3" size	80mm	3.15 O.D. x 2.98 I.D
4" size	101mm	4.00 O.D. x 3.78 I.D
6" size	153mm	6.02 O.D. x 5.75 I.D
8" size	203mm	8.07 O.D. x 7.69 I.D

### Fitting Specifications:

#### Compression Style

3/4" thru 2" Body: nylon 6 with fiberglass reinforcement, blue color

3" Body: Diecast aluminum, then electrocoated, black color

Bite Ring: stainless steel

O-Ring: nitrile



#### Compression Style

3" Body: Diecast aluminum, then electrocoated, black color

Bite Ring: stainless steel

O-Ring: nitrile



#### Lug Style

4" - 8" Body: Diecast aluminum/Steel, Powdercoat

Inner Seal: nitrile



PRODUCTS MANUFACTURED BY THE SELLER CARRY A LIMITED ONE YEAR WARRANTY

RapidAir Products | [www.rapidairproducts.com](http://www.rapidairproducts.com)  
6111 Mill Creek Drive Auburndale, WI 54412 | 800-954-3310